## Hygienic Floor Squeegee w/replacement cassette, 23.6", Red







Designed for areas where both high levels of hygiene and effective water removal are required, this squeegee can be used on all types of surfaces, including tiled and safety flooring. The cassette can be removed easily for cleaning or replacement (Series 7734 for replacement blades).

## **Technical Data**

Item Number	77144
Material	Polypropylene TPE Rubber
Complies with (EC) 1935/2004 on food contact materials <sup>1</sup>	Yes
Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
FDA-compliant raw material (CFR 21)	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
Use of phthalates and bisphenol A	No
Is Halal and Kosher compliant	Yes
Pat. Pending/Patent No.	EP2227129 validated in DK, DE, FR and GB. DE 602008048400.9
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	320 Pcs.
Quantity Per Layer (Pallet)	40 Pcs.
Length	23.6 "
Width	3.1 "
Height	4.3 "
Net Weight	0.7496 lbs
Weight bag (Recycling Symbol "4" Low Density Polyethylene (LDPE)	0.2 lbs
Weight cardboard (Recycling symbol "20" PAP)	0.08 lbs
Tare Total	0.28 lbs
Gross Weight	1.0291 lbs
Cubic Feet	0.1866 ft3
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (food contact)	122 °F
Max usage temperature (non food contact)	212 °F
Min. usage temperature	-4 °F
Max. drying temperature	248 °F
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705020771446
GTIN-14 Number (Box quantity)	15705020771443
Customs Tariff No.	96039099
Country of Origin	Denmark

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

- 1. See Declaration of Compliance for further details on food contact
- 3. Do not store the product below 32 °Fahrenheit.